





Max cutting capacity in cement fiber siding 13 mm (1/2")



Cuts up to 13 mm (1/2") cement fiber siding



Single LED job light

with afterglow function illuminates the work area.







360 degree swivel shear head

Increased maneuverability achieved by using a 360 degree swivel shear head which is 12 position adjustable according to the orientation of workpiece and user's work posture.



Ergonomically designed handle

with soft grip provides increased comfort on the job.



Hook

Durable, reversible belt clip convenient for temporary tool hanging.





Accessories

Side blade Part No. 725260-0



Center blade

Part No. 725259-5



Hook

for BL1830B, BL1840B, BL1850B, BL1860B Part No. 346317-0

for BL1820B, BL1815N Part No. 346449-3





Charging Time

18V	DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 _{min}	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 _{min}	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Cement Shear

Cordiess Cement Shear

Wariable Speed	
Built-in Job Ligh	n

DJS800 13 mm (1/2")

 Max Cutting Capacity
 13 mm (1/2")

 Strokes Per Minute (SPM)
 0 - 3,000

 Dimensions (L x W x H)
 w/BL1815N/BL1820B:

 379 x 79 x 198 mm
 (14-7/8 x 3-1/8 x 7-3/4")

 W/BL1830B/BL1840B/BL1850B/BL1850B/BL1850B/BL1850B/SY216 mm
 (14-7/8"x3-1/8"x8-1/2")

 Net weight
 2.1 - 2.5 kg (4.6 - 5.5 lbs.)

Standard Equipment: Hex Wrench, Belt Clip, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan