



Cordless Flashlight ML006G / DML816



XGT
40V LXT max
Li-ion

18V
LITHIUM-ION



**Max luminous flux:
500 lm**



ML006G
XGT 40V LXT max
Li-ion

DML816
18V LITHIUM-ION

Continuous run time (approx) on a full battery charge	
ML006G 51 h Battery: BL4025 Low mode	DML816 75 h Battery: BL1860B Low mode




Max luminous flux
500 lm

Rotatable and foldable light head



Foldable light head



Rotatable light head
(90° right and 180° left)



Can be used as a compact stationary lamp with the light head swivelled and folded fully.

ML006G



DML816



Light diffusing lens

- softens the light of LED to reduce glare.
- provides widespread illumination.



Large hook

Light head is rotatable with the flashlight hanging down.



Retractable back into the upper portion of handle

Battery capacity warning

This system warns user by reducing the number of ON LED lights down to 1 before the battery is empty.

3-stage brightness adjustment

High → Medium → Low → OFF

Accessories

Lamp shade

Part No. GM00001326

By attaching to the Cordless Flashlight ML006G / DML816, the irradiation range is widened and the glare of the light source is reduced.



without Lamp shade

with Lamp shade

Shoulder hook set

Part No. GM00001288



Charging Time

	Fast Charging DC40RC			Fast Charging DC18RC	
	DC40RA	DC40RC		DC18RC	DC18SD
BL4020 2.0Ah	22 min	30 min	BL1815N 1.5Ah	15 min	30 min
BL4025 2.5Ah	28 min	38 min	BL1820B 2.0Ah	24 min	45 min
BL4040 4.0Ah	45 min	67 min	BL1830B 3.0Ah	22 min	60 min
BL4050F 5.0Ah	50 min	85 min	BL1840B 4.0Ah	36 min	90 min
			BL1850B 5.0Ah	45 min	110 min
			BL1860B 6.0Ah	55 min	130 min

Cordless Flashlight

ML006G / DML816

	ML006G	DML816
Run Time (hrs)	Up to: 82 (Low mode, with BL4040)	Up to: 75 (Low mode, with BL1860B)
Illuminance (at 0.5m from the light source)	High/ Medium/ Low: 800 / 400 / 180 lx	High/ Medium/ Low: 800 / 400 / 180 lx
Luminous Flux	High/ Medium/ Low: 500 / 250 / 100 lm	High/ Medium/ Low: 500 / 250 / 100 lm
Dimensions (L x W x H)	w/ BL4040: 275 - 408 x 85 x 148 mm (10-7/8 - 16 x 3-3/8 x 5-7/8")	w/ BL1830B / BL1840B / BL1850B / BL1860B: 267 - 400 x 79 x 127 mm (10-1/2 - 15-3/4 x 3-1/8 x 5")
Net weight	1.1 - 1.7 kg (2.4 - 3.8 lbs.)	0.70 - 1.1 kg (1.5 - 2.4 lbs.)

Standard Equipment : Shoulder hook set, Lamp shade

not covered by EPTA-Procedure
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202110