



Light section can be attached to Battery holder section using Swivel clip.





IPX-4 waterproof design

(Head light section only)

resists splashing water such as a sudden shower, etc.



2 stage push-button switch

enables to select high/low brightness.



Swivel hook on Light section enables to hook the light section on a jacket, etc at any angle.



Low - 18, **High** - 12 with BL1430 (3.0Ah)

Low - 8, **High** - 5 with BL1415 (1.3Ah)

Light section (without Clip):

Battery holder section:

Battery holder section: 0.75kg (1.7lbs) with BL1430

0.58kg (1.3lbs) with BL1415

133x81x89mm

133x81x72mm

99x62x25mm (3-7/8"x2-7/16"x1")

(5-1/4"x3-3/16"x3-1/2") with BL1430

Battery









BL1830: 18V 3.0Ah

Charger

BI 1815: 18V 1 3Ah

BL1430: 14.4V 3.0Ah BL1415: 14.4V 1.3Ah

DC18RC / DC18RA



DC18SF

Charging time (3.0Ah) 1 to 2 batteries : 60minutes 3 to 4 batteries: 120minutes

DC18SD Charging time (3.0Ah) 60minutes



LED Flashlight

BML803 18V, 14.4V



(5-1/4"x3-3/16"x2-13/16") with BL1415 Light section (with cord): 0.12kg (0.3lbs) Light section (with cord): 0.12kg (0.3lbs)

Standard Equipment: Battery and Charger are sold separately.

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan