



Cordless Hammer Driver Drill
Cordless Driver Drill
Cordless Impact Driver

Satisfy Professional's Needs

LXT
LITHIUM-ION

18V
LITHIUM-ION

XPT
EXTREME PROTECTION TECHNOLOGY



Cordless Hammer Driver Drill
DHP482

Cordless Driver Drill
DDF482

Cordless Impact Driver
DTD152

Bits are option.

High Speed



DHP482

1,900 High Speed

Predecessor model: 1,500



DDF482

1,900 High Speed

Predecessor model: 1,500



DTD152

2,900 High Speed

Predecessor model: 2,300

Compact overall length for increased maneuverability

← 198mm(7-3/4") DHP482 →

LED Job light with pre-glow functions

On pulling switch trigger, the light automatically turns on before motor starts turning.



Compact belt clip

XPT
EXTREME PROTECTION TECHNOLOGY

For use in outdoor applications or harsh environments, protection from dust and dripping water is enhanced.



Battery

with Battery fuel gauge
BL1850B : 5.0Ah
BL1840B : 4.0Ah
BL1820B : 2.0Ah



BL1850B

BL1850 : 5.0Ah
BL1840 : 4.0Ah
BL1830 : 3.0Ah
BL1820 : 2.0Ah
BL1815N : 1.5Ah



BL1820B

Fast Charger

DC18RC

Charging time 22min.



Charger

DC18SD

Charging time 60min.



More Torque

DTD152: 165N·m

Predecessor model: 160N·m

DHP482/DDF482: 62N·m

Predecessor model: 50N·m (Hard Joint)

Ergonomically designed handle with soft grip



A In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened according to the U-shape formed between user's thumb and index finger.

B Rubberized soft grip provides comfortable grip and more control while minimizing hand fatigue and pain.

All metal gear construction

All metal gear construction for extra-high transmission durability

(DHP482, DDF482)



21 stages Torque Settings

(DHP482, DDF482)

Predecessor model: 16 stages



Cordless Hammer Driver Drill

Cordless Driver Drill

DHP482 13mm (1/2")

440

DDF482 13mm (1/2")

440

- Variable Speed
- Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 21
- Built-in Job Light
- Carrying Case



DDF482

← 185mm(7-1/4") →

	DHP482	DDF482
Capacity	Steel : 13mm (1/2") Wood : 38mm (1-1/2") Masonry : 13mm (1/2")	Steel : 13mm (1/2") Wood : 38mm (1-1/2")
Impacts per minute (ipm)	Hi : 0-28,500 Lo : 0-9,000	-
No load speed (rpm)	Hi : 0-1,900 Lo : 0-600	Hi : 0 - 1,900 Lo : 0 - 600
Max. fastening torque	Hard / Soft : 62 / 36N.m	Hard / Soft : 62 / 36N.m
Dimensions (L x W x H)	198x79x249mm (7-3/4"x3-1/8"x9-3/4")	185x79x249mm (7-1/4"x3-1/8"x9-3/4")
Net Weight*	1.5kg (3.4lbs) with BL1815N 1.8kg (3.9lbs) with BL1850	1.5kg (3.3lbs) with BL1815N 1.7kg (3.8lbs) with BL1850

Standard Equipment : Fast Charger, Battery Cartridge, (+) (-) Bit, Belt clip

Cordless Impact Driver

DTD152

448

- Variable Speed
- Brake
- Reversing
- Built-in Job Light
- Carrying Case



← 137mm (5-3/8") →

Capacity	Machine screw : M4 - M8 (5/32 - 5/16") Standard bolt : M5 - M16 (3/16 - 5/8") High tensile bolt : M5 - M12 (3/16 - 1/2") Coarse thread (in length) : 22 - 125mm (7/8 - 4-7/8")
Impacts per minute (ipm)	0 - 3,500
No load speed (rpm)	0 - 2,900
Max. fastening torque	165N.m
Dimensions (L x W x H)	137x79x238mm (5-3/8"x3-1/8"x9-3/8")
Net Weight*	1.3kg (2.8lbs) with BL1815N 1.5kg (3.3lbs) with BL1850

Standard Equipment : Fast Charger, Battery Cartridge, Belt clip

*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 2015-07