



# Cordless Area Worklight ML010G 40Vmax, 18V, 14.4V / AC



# 40V<sup>Li-ion</sup> max

# 18V LITHIUM-ION

## Improved Self-righting performance



## Up to 4 batteries can be installed in parallel.

two LXT batteries + two XGT batteries



## Continuous run time (approx)

Low mode **59** hours

Battery: BL4080F x2 & BL1860B x2  
all LEDs light up



Max luminous flux

**5,500** lm





**Compatible with 3 power sources**



**AC**



two in parallel or one



two in parallel or one



Inlet type AC power supply cord

**3 brightness settings**

with memory function of the setting last time you power off



Low

1,500 lm



Medium

3,000 lm



High

5,500 lm

**Lighting area selection**



left  
180°



360°



right  
180°

**Continuous run time (approx)**

all LEDs light up

Battery	High	Medium	Low
BL1860B x2	4.5 h	8.5 h	16 h
BL4040 x2	6.5 h	11 h	21 h
BL4050F x2	8.5 h	14 h	27 h
BL4040 x2 + BL1860B x2	11 h	19.5 h	37 h
BL4050F x2 + BL1860B x2	13 h	22.5 h	43 h
BL4080F x2	13 h	23 h	43 h
BL4080F x2 + BL1860B x2	17.5 h	-	59 h

Battery capacity warning function



Hook for power cord



Battery fuel gauge



Padlock hole anti-battery theft



Diffusing lens  
Daylight white  
(approx 5,500K)

Carrying handle



Reflector  
glows in the dark to help you locate the worklight body.

AC outlet allows for connecting up to 8 units of this light together.



IP54-rated water resistance  
(Only with DC power supply)



**Charging Time**

	Fast Charging				Fast Charging		
	DC18RC DC18RD	DC18SD			DC40RA DC40RB	DC40RC	DC40WA
<b>BL1815N</b> 1.5Ah	<b>15 min</b>	<b>30 min</b>		<b>BL4020</b> 2.0Ah	<b>22 min</b>	<b>30 min</b>	<b>110 min</b>
<b>BL1820B</b> 2.0Ah	<b>24 min</b>	<b>45 min</b>		<b>BL4025</b> 2.5Ah	<b>28 min</b>	<b>38 min</b>	<b>130 min</b>
<b>BL1830B</b> 3.0Ah	<b>22 min</b>	<b>60 min</b>		<b>BL4040</b> 4.0Ah	<b>45 min</b>	<b>67 min</b>	<b>210 min</b>
<b>BL1840B</b> 4.0Ah	<b>36 min</b>	<b>90 min</b>		<b>BL4050F</b> 5.0Ah	<b>50 min</b>	<b>85 min</b>	<b>260 min</b>
<b>BL1850B</b> 5.0Ah	<b>45 min</b>	<b>110 min</b>		<b>BL4080F</b> 8.0Ah	<b>76 min</b>	<b>170 min</b>	<b>420 min</b>
<b>BL1860B</b> 6.0Ah	<b>55 min</b>	<b>130 min</b>					

Not covered by EPTA-Procedure

Items of standard equipment and specifications may vary by country or area.

**Cordless Area Worklight**

**ML1010G 40Vmax, 18V, 14.4V / AC**

Illuminance (High / Med. / Low)	at 1 m from the light source: 550 / 300 / 150 lx
Luminous flux	High / Med. / Low: 5,500 / 3,000 / 1,500 lm
Continuous run time on full battery charge	High / Med. / Low, w/ BL1860B x2: 4.5 / 8.5 / 16 hours High / Med. / Low, w/ BL4040 x2: 6.5 / 11 / 21 hours High / Med. / Low, w/ BL4050F x2: 8.5 / 14 / 27 hours High / Med. / Low, w/ BL4040 x2 & BL1860B x2: 11 / 19.5 / 37 hours High / Med. / Low, w/ BL4050F x2 & BL1860B x2: 13 / 22.5 / 43 hours High / Med. / Low, w/ BL4080F x2: 13 / 23 / 43 hours
Dimensions (L x W x H)	490 x 490 x 814 mm (19-1/4 x 19-1/4 x 32")
Net weight	14.4 - 19.2 kg (31.7 - 42.3 lbs.)
Power supply cord	2.5 m (8.2 ft)

Standard Equipment : AC power cord, Earth grounding plug

Battery & Charger Sold Separately

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202306