



# High cutting efficiency with LXT 18V battery



# **Compact and lightweight**



# Powerful enough to perform smooth light duty cuts

Variable speed control by trigger

Makes it easier to align with cutting lines.

Change lever for 3 orbital settings and straight cutting

Optimum cutting action can be selected simply by turning the lever.



Stroke length: 18mm

## **Blower function**

**Guide rail set** 

Length

1.0m

1.4m

1.5m

1.9m

3.0m



191J16-7 / 199140-0

191J17-5 / 194368-5

199141-8

194925-9 / 194926-7

194367-7


Charging Time



Length		
1.4m	191J53-1 / 194418-6	
1.9m	194910-2 / 194915-2	
3.0m	194419-4	



Sheet 10000 set



Length	Part No.
1.4m	191J53-1 / 194418-6
1.9m	194910-2 / 194915-2
3 0m	10//10_/



**Rubber sheet** 10000 set


191J54-9 / 194417-8

**Push clamp set** 

Makita


# Battery and charger

Part No.





<u>LXT</u>



BLB182 2.0Ah



**90** min

DCB18WA

# compatibility




Charge the LXT batteries with the LXT battery chargers and the LXT BASIC battery with the LXT BASIC battery charger.

### Powered by 18V LXT Soft grip Li-lon battery

## **Connectable to** a vacuum cleaner



# Rigid aluminum base



# Accessories

## Support base set

- Reduces unstable tilting of the blade during bevel cuts, enabling stable cutting.
- Enhances the precision of curved cuts.

Part No. 1915R3-2





**Guide rule set** 

Part No. 192732-4







# **Cordless Jig Saw**

## **DJV186**

**Guide rail** 

Part No.

198704-7

adapter set

For use with guide rails

Variable Speed	Stroke length	18 mm (11/16")
	Strokes per minute	0 - 2,900 min <sup>-1</sup>
(RAKE) Brake	Capacity	Wood: 65 mm (2-9/16")
		Mild steel: 6 mm (1/4")
Orbital Cutting		Aluminum: 10 mm (3/8")
•	Bevel range	0 - 45 °
Bayonet Shank Jig Saw Blade	Vibration level*	Cutting boards: 7.5 m/s <sup>2</sup> ,
B Saw Blade		Cutting sheet metal: 4.2 m/s <sup>2</sup>
Dust Collection	Vibration K factor*	Cutting boards: 1.5 m/s <sup>2</sup> ,
Dust Collection		Cutting sheet metal: 1.5 m/s <sup>2</sup>
Carrying Case	Sound pressure level*	85 dB(A)
Carrying Case	Sound power level*	93 dB(A)
	Noise K factor *	3 dB(A)
	Dimensions	241 - 257 x 81 x 196 mm
	(LxWxH)	(9-1/2 - 10-1/8 x 3-3/16 x 7-3/4")
	Battery	BLB182 - BL1860B
	Net weight	1.9 - 2.2 kg (4.2 - 4.9 lbs.)
	Battery	BL1815N - BL1860B
*EN62841-2-11		

Standard Equipment: Jig saw blade, Hex wrench, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge.

The lightest and heaviest combination are shown in the table.

PRINTED IN JAPAN 202506

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan



回霧線回