



Cordless Breaker HM004G

Satisfy Professional's Needs



28.6mm Hex
Shank Type

40V^{Li-ion} max + 40V^{Li-ion} max



High power similar to corded models

Impact energy

72.8 Joule

Low Vibration

6.5 m/s²

BL MOTOR **AVT** **AWS** **SOFT** NOLOAD **XPT**

XGT X2
80Vmax

40V Li-ion max + 40V Li-ion max



Powered by two 40Vmax XGT
Li-ion batteries in series
(80Vmax)

**BL
MOTOR**

High power
brushless
motor

Impact energy
72.8 Joule



AWS

(Auto-start Wireless System)

Connects to compatible vacuum cleaner with Bluetooth.
The vacuum cleaner automatically runs while the switch is on.

Bluetooth®



Accessories

Dust extractor attachment set

w/o hose

Part No. 197168-2

** 197170-5

w/ hose

Part No. 197148-8

** 197172-1

**With Sensormatic chip



Charging Time

	Fast Charging			
	DC40RA	DC40RB	DC40RC	DC40WA
BL4020 2.0Ah	22 min	30 min	110 min	
BL4025 2.5Ah	28 min	38 min	130 min	
* ¹ BL4040/F 4.0Ah	45 min	67 min	210 min	
* ¹ BL4050F 5.0Ah	50 min	85 min	260 min	
* ¹ BL4080F 8.0Ah	76 min	170 min	420 min	

*¹ Recommended battery

Low Vibration
thanks to

AVT

(Anti-Vibration Technology)


Vibration level **6.5 m/s²**

Active dynamic vibration absorber moves in the opposite direction to the drive piston to reduce vibration.

Vibration absorbing housing


provides a practical combination of high power and low vibration.

Vibration absorbing spring (4 places)




Counter weight mechanism

reduces vibration during chipping operation.




**SOFT
NO LOAD**

Suppression of motor speed during no-load




During no-load



Under load

Main power switch

Battery capacity warning lamp



Maintenance warning lamp

LED job light

Twin LEDs with preglow and afterglow functions



XPT

(eXtreme Protection Technology)



Cordless Breaker

HM004G 1-1/8" : 28.6mm Hex Shank

28.6mm Hex Shank

Constant Speed

Soft Start

Built-in Job Light

Anti-restart function

Impact energy	72.8 J (53.7 ft.lbs.)
Blows per minute (BPM)	870
Shank diameter	28.6 mm (1-1/8")
Sound power level	103 dB(A) (Uncertainty (K): 1.62 dB(A))
Sound pressure level	95 dB(A) (Uncertainty (K): 1.62 dB(A))
Vibration level	6.5 m/s ² (Uncertainty (K): 1.5 m/s ²)
Dimensions (L x W x H)	882 x 227 x 540 mm
	(34-3/4 x 8-15/16 x 21-1/4")
Net weight	29.7 - 32.1 kg (65.5 - 70.8 lbs.)

Standard Equipment : Hex wrench, Bull point, Wireless unit set

The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202404



www.makita.com