






- The ram automatically retracts to its original position after completing the crimping operation, enhancing work efficiency.
- The On/Off setting of the auto retract function can be switched.



The tool head is capable of rotating 360 degrees.



### Release knob

To retract the ram manually, press the release knob.



## LED job light

Single LED with afterglow function



# Switch trigger Trigger-lock function

Thakita

Strap

Straps on the tool for

shoulder strap

attaching the optional

Trigger-lock function to minimize accidental pulling of the switch trigger

Soft grip provides increased comfort during use



## Cordless Crimper Series

DTC301 with dies (U-type)

Crimping capacity

Cu Ø19.5 mm (300mm²)

Al Ø19.5 mm (300mm²)



## DTC302 with dies (U-type)

Crimping capacity

Ø22.5 mm (400mm²)

Ø19.5 mm (300mm²)



## DTC303 without dies

Crimping capacity

Cu Ø17.5 mm (240mm²)

Ø17.5 mm (240<sub>mm²</sub>)



#### Accessories

## **Shoulder belt**

Part No. 161347-8



## Charging Time

TEV PLANTIUM HON	DC18RC	DC18SD
<b>BL1815N</b> 1.5Ah	15 min	30 min
<b>BL1820B</b> 2.0Ah	24 <sub>min</sub>	45 min
<b>BL1830B</b> 3.0Ah	22 min	60 min
<b>BL1840B</b> 4.0Ah	36 min	90 min
<b>BL1850B</b> 5.0Ah	45 min	110 min
<b>BL1860B</b> 6.0Ah	55 min	130 min

## **Cordless Crimper**

#### **DTC30**:

D1C303	
Built-in Job Light  Carrying Case	Output force Crimping capacity Dimensions (L x W x (Battery) Net weight (Battery)

60 kN Cu: ø17.5 mm (240 mm²) Al: ø17.5 mm (240 mm²) 401 x 82 x 348 mm (15-3/4 x 3-1/4 x 13-3/4") Bl 18608

(15-3/4 x 3-1/4 x 13-3/4") BL1860B 5.3 - 5.7 kg (11.7 - 12.6 lbs.) BL1815N - BL1860B

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combinations are shown in the table.

Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

Standard Equipment : Battery, Charger

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

