




Cordless Driver Drill DDF491 13 mm (1/2")

Satisfy Professional's Needs

LXT

4 tools in 1 Maximum versatility
for any job.

18V
LITHIUM-ION



BL MOTOR **XPT**

Four quick-change heads



let you drill, drive, and work in tight spaces—without the need for additional tools.

4 tools in 1

Drill chuck attachment set Part No. 1918F1-0

Keyless drill chuck with metal single-sleeve for basic drilling and screwdriving

Hex bit attachment set Part No. 1918F2-8 (M type) Part No. 1918F3-6 (N type)

Compact design for screwdriving in tight spaces
Toolless quick bit replacement with push-in installation and pull-sleeve release

Offset attachment set

Adjustable to 16 different angles every 22.5 degrees when installed on the tool Part No. 1918F4-4 (M type)
Part No. 1918F5-2 (N type)

Compact design for screwdriving in corners and tight spaces
Toolless quick bit replacement with push-in installation and pull-sleeve release

Angle attachment set

Adjustable to 16 different angles every 22.5 degrees when installed on the tool Part No. 1918F6-0


Compact design for screwdriving in tight spaces

Accepts connection of the other three attachments



Usable even without attachments.

A C-form driver bit is securely held by a built-in magnet.



Max fastening torque

65 N·m

20-stage torque settings allow for fine adjustments to suit the task at hand.

Mechanical 2-speed

LED job light

Variable speed control by trigger allows for speed adjustments based on the material or application.



(eXtreme Protection Technology)

Charging Time

	Fast Charging DC18RC	DC18SD
18V LITHIUM-ION		
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min
18V LITHIUM-ION	LXT BASIC	DCB18WA
Compatible with charger DCB18WA only		
BLB182 2.0Ah		90 min

Charge the LXT batteries with the LXT battery chargers and the LXT BASIC battery with the LXT BASIC battery charger.

Cordless Driver Drill

DDE491 13 mm (1/2")

- Variable Speed
- Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 20
- Built-in Job Light
- Carrying Case

*EN62841-2-1, Mode:
Drilling into metal,
Attachment type: Drill
chuck attachment

No load speed	High: 0 - 1,900 min ⁻¹ Low: 0 - 500 min ⁻¹ Wood (Self-feed bit): 38 mm (1-1/2") Steel: 13 mm (1/2")
Capacity	
Max fastening torque	Max: 65 N·m (580 in.lbs.) Hard: 50 N·m (440 in.lbs.) Soft: 27 N·m (240 in.lbs.) 13 mm (1/2")
Chuck capacity	13 mm (1/2")
Vibration level	2.0 m/s ² *
Uncertainty (K) for Vibration	1.5 m/s ² *
Sound pressure level	79 dB(A) (EN62841-2-1)
Sound power level	87 dB(A) (EN62841-2-1)
Uncertainty (K) for Noise	3 dB(A) (EN62841-2-1)
Dimensions (L x W x H) (Battery)	186 x 81 x 255 mm (7-3/8 x 3-3/16 x 10") (BL1850B)
W/Drill chuck attachment	
Net weight (Battery)	1.8 kg (4.0 lbs.) (BL1850B)

Standard Equipment : Hook, Phillips bit, Drill chuck attachment, Hex bit attachment, Offset attachment, Angle attachment

Standard equipment and accessories, product appearance and specifications may vary by country or region, and all test results, including work amount per charge and work efficiency, are for reference only and may vary depending on application and operating conditions.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan



PRINTED IN JAPAN 202607

www.makita.com