



Cordless Impact Wrench DTW210 12.7 mm (1/2")

Satisfy Professional's Needs



Compact Size. Professional Power.



Photo: DTW210 with BLB182

Max fastening torque

Battery: BLB182

230 N·m*

Battery: BL1860B

250 N·m*

*Tightening torque at 6 seconds after seating, when tightening M16 Hex bolt (grade 10.9)



*Except when the BLB182 battery is installed

Built Compact. Designed for Control.

**BL
MOTOR**

High-power
brushless motor




Driving shank
12.7 mm (1/2") Square drive,
C ring, with Pin hole

LED job light
• Twin LEDs
• With preglow and
afterglow functions

Net weight
1.3 kg
Battery: BLB182

Optimal battery location

Compared with the current DTW190, the battery has been repositioned closer to the grip centerline, helping reduce wrist strain during operation.



Center of gravity



* The same features and benefits as those of DTW190.
Photo: DTW210 with BLB182

Charging Time

	Fast Charging DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min
	LXT BASIC DCB18WA	
BLB182 2.0Ah	90 min	

Charge the LXT batteries with the LXT battery chargers and the LXT BASIC battery with the LXT BASIC battery charger.

Cordless Impact Wrench DTW210 12.7 mm (1/2")

- Variable Speed
- Brake
- Reversing
- Built-in Job Light
- Carrying Case

*EN62841-2-2, Mode: impact tightening of fasteners of the maximum capacity of the tool

Shank / Drive	Square Drive 12.7 mm (1/2")
No load speed	0 - 2,300 min ⁻¹
Fastening capacities	Standard bolt: M5 - M16 (3/16 - 5/8"), High strength bolt: M5 - M14 (3/16 - 9/16")
Max fastening torque (Battery)	230 N·m (170 ft.lbs.) (BLB182) 250 N·m (180 ft.lbs.) (BL1860B)
Nut-busting torque (Battery)	350 N·m (260 ft.lbs.) (BLB182) 400 N·m (300 ft.lbs.) (BL1860B)
Impacts per minute	0 - 3,200 min ⁻¹
Vibration level (Uncertainty (K))	8.0 m/s ² * (1.5 m/s ² *)
Sound pressure level	98 dB(A) (EN62841-2-2)
Sound power level	106 dB(A) (EN62841-2-2)
Uncertainty (K) for Noise	3 dB(A) (EN62841-2-2)
Dimensions (L x W x H)	130 x 81 x 233 - 250 mm
(Battery)	(5-1/8 x 3-3/16 x 9-1/8 - 9-7/8")
Net weight (Battery)	(BLB182 - BL1860B) 1.3 - 1.6 kg (2.9 - 3.5 lbs.) (BLB182 - BL1860B)

Standard equipment and accessories, product appearance and specifications may vary by country or region, and all test results, including work amount per charge and work efficiency, are for reference only and may vary depending on application and operating conditions.

**18V
LITHIUM-ION**

XPT

*Except when the BLB182 battery is installed

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan



PRINTED IN JAPAN 202608

www.makita.com